

HIRO

GDO-12



COMMERCIAL ROLLER DOOR OPENER

Powerhouse performance for demanding applications.

Slim but powerful to suit demanding business and commercial applications. Despite being one of the most powerful openers in our range, the Hiro is also suitable for low side room installation, making it versatile and excellent for tight spaces.

The Hiro opener delivers both control and connectivity via an in-built smartphone control system. Whether you have a very large roller door, a wind-locked door or require low side room compatibility, the Hiro opener is the perfect choice for commercial and industrial needs.

WHAT'S INCLUDED:



Opener with LED Courtesy Light



Wireless wall button + 2x TrioCode™ 128 Remote Controls



Wired Safety Beams

AT A GLANCE:



SECURE & RELIABLE TRANSMITTERS

The TrioCode™128 transmitter system ensures secure and reliable home access. It transmits on three frequencies to defeat radio interference, and uses a 128-bit encryption protocol for the ultimate in security.

KEY FEATURES

- 1400N Short-term peak force
- Soft Start / Soft Close
- Slim fit design
- LED Courtesy Light
- Intelligent Safety System
- Smart phone compatible

INTELLIGENT SAFETY SYSTEM (ISS)

If contact is made with an obstruction while moving, the opener either stops or reverses the door to reduce the risk of injury or property damage.

SOFT START / SOFT CLOSE

The Soft Start / Soft Close feature ramps speed up and down at the start and end of each cycle, therefore reducing stress on the door and opener.

TECHNICAL SPECIFICATIONS



HIRO GDO-12

Power	Input Voltage	230-240V a.c. 1-phase
	Motor Type	24V d.c. Permanent Magnet
	Standby Power	2.8W
	Transformer Rating	150VA
Door Sizes	Rated Door Area	28 m ²
	Typical Travel Speed	Variable via control panel
Transmitter System	Receiver/Transmitter Frequency	Multi-frequency UHF FM (433.47, 433.92 & 434.37MHz)
	Coding System	TrioCode™ 128, code hopping
	Code Combinations	3.4x10 ³⁸ code combinations
	Transmitter Capacity (x 4-button registers)	511
Additional Features	Courtesy Light	Output available
	Safety Beam Compatibility	3xwireless/ 2-wire Safety Beams
	LCD Screen	Yes
Optional Accessories	Battery backup	Optional
	Smart Phone Control Kit	Optional
Warranty*	2 year/10,000 cycles	

SAFETY & SECURITY FEATURES

- Soft Start/Soft Stop (inverter units only)
- Door Profiling
- TrioCode™128
- Network ready

POWER & MOUNTING SYSTEM

- DC Motor
- Battery Backup

OPERATING MODES

- Service Indicator
- Courtesy Light Output
- Auto Close
- Vacation Mode
- AUX Auxiliary Output

OPTIONS AND UPGRADES



SMART PHONE CONTROL KIT

Monitor and operate your rolling door on your smart phone from anywhere.



BATTERY BACKUP

In the event of power failure, your door will still operate.



KEYPAD

Weather proof, entry keypad ensures secure access without transmitter or key.

For more product information, visit www.automatictechnology.com/au

©2024 Automatic Technology (Australia) Pty Ltd. All rights reserved. The Automatic Technology logos, feature icons & TrioCode™ are registered trademarks. In an ongoing commitment to product quality, the specifications may change from time to time – E&OE Automatic Technology (Australia) Pty Ltd, 6-8 Fiveways Boulevard, Keysborough VIC 3173, www.automatictechnology.com.au, 1300 133 944. *Please see full warranty terms and conditions at www.automatictechnology.com/au. This brochure is not evidence of our warranty. Our warranty is in addition to any consumer guarantees that may apply under the Australian Consumer Law. Date: November 2024

autOmatic
TECHNOLOGY®