

HIGH ROLLING SHEET DOORS

Powerhouse performance for demanding applications

Slim but powerful to suit demanding business and commercial applications. Despite being one of the most powerful openers in our range, the Hiro is also suitable for low side room installation, making it an excellent option for tight spaces with as little as 1.57 inches.

The Hiro opener delivers both control and connectivity via an in-built smartphone control system. Whether you have a very large roller door, a wind-locked door or require low side room compatibility, the Hiro opener is the perfect choice for commercial and industrial needs.

WHAT'S INCLUDED:



Opener with LED Courtesy Light



Wireless wall button + 2x TrioCode™ 128 Remote Controls



Wired Safety Beams

AT A GLANCE:

SECURE & RELIABLE TRANSMITTERS

The TrioCode[™]128 transmitter system ensures secure and reliable home access. It transmits on three frequencies to defeat radio interference, and uses a 128-bit encryption protocol for the ultimate in security.

KEY FEATURES

- 1400N Short-term peak force
- Soft Start / Soft Close
- Slim fit design
- · LED Courtesy Light
- Intelligent Safety System
- Smart phone compatible

INTELLIGENT SAFETY SYSTEM (ISS)

If contact is made with an obstruction while moving, the opener either stops or reverses the door to reduce the risk of injury or property damage.

SOFT START / SOFT CLOSE

The Soft Start / Soft Close feature ramps speed up and down at the start and end of each cycle, therefore reducing stress on the door and opener.



TECHNICAL **SPECIFICATIONS**



DOMINATOR™ HIRO

Power	Input Voltage	120 V
	Motor Type	24V d.c. Permanent Magnet
	Current (max)	2A
	Controller Fuse	10A
	Short-Term Peak Force	1400N
Installation¹	Door Size	300 ft ²
	Door Size (wind-lock)	236 ft ²
Transmitter System	Receiver/Transmitter Frequency	Multi-frequency UHF FM (433.47, 433.92 & 434.37MHz)
	Coding System	TrioCode™ 128, code hopping
	Code Combinations	3.4x10 ³⁸ code combinations
	Transmitter Capacity (x 4-button registers)	64
Features	Courtesy Light	LED
	Safety Beam Compatibility	2-wire Safety Beams
	Installation	Suits most sheet doors
Optional Accessories	Battery backup	Optional
	Smart Phone Control Kit	Optional
Warranty*	2 year/10,000 cycles on parts 1 year on accessories	

SAFETY & SECURITY **FEATURES**



Soft Start/Soft Stop (inverter units only)



Door Profiling



TrioCode™128



Network ready

POWER & MOUNTING SYSTEM



DC Motor



Battery Backup

OPERATING MODES



Service Indicator



Courtesy Light Output



Auto Close



Vacation Mode



AUX Auxiliary Output

OPTIONAL ACCESSORIES



AUTO-KISMART PHONE CONTROL KIT

Monitor and operate your rolling door on your smart phone from anywhere#



BATTERY BACKUP

In the event of power failure, your door will still operate.



KEYPAD

Weather proof, entry keypad ensures secure access without transmitter or kev.









- Please note, suitable for use on dead axle doors only and windy conditions may trigger the obstruction feature on the opener.
 Please see full warranty terms and conditions on our website. This brochure is not evidence of our warranty. Our warranty is in addition to any consumer guarantees that may apply under American Law.





