

SUITABLE FOR USE ON ROLLING SHEET DOORS

YOUR 'GO TO' ROLLING DOOR OPENER

Our flagship rolling door opener, the Dominator EasyRoller 14[™] features a slim profile, reliability, security and convenience. The slim-fit chassis suits low side room installations.

The Dominator EasyRoller 14TM incorporates bright LED courtesy lighting. The opener comes with Soft Start/Soft Stop operation, advanced door profiling and obstruction sensing for secure and safe operation. The Service Indicator lets you know when it is time to service your door. EasyRoller 14TM is suitable for use on doors up to 14ft.

WHAT'S INCLUDED:



Opener with LED Courtesy Light



Wireless wall button and Two TrioCode™ 128 Remote Controls



Adaptors for multiple sheet door drum types



Safety Beams

AT A GLANCE:



SECURE & RELIABLE TRANSMITTERS

The TrioCode™ 128 remote control ensures secure and reliable home access. It transmits on three frequencies to defeat radio interference, and uses a 128-bit encryption protocol (with trillions upon trillions of random codes*) for the ultimate in security.



*340,282,366,920,938,463,463,374,607,431,768,211,456 codes

KEY FEATURES

- 600N DC Motor
- Soft Start / Soft Close
- Slim fit design
- LED Courtesy Light
- Intelligent Safety System

ADAPTORS AVAILABLE TO SUIT DIFFERENT DOOR TYPES

Opener comes with adaptors for most sheet door drum types as well as an optional Live Axle Kit to suit live axle doors.

INTELLIGENT SAFETY SYSTEM (ISS)

If contact is made with an obstruction while moving, the opener either stops or reverses the door to reduce the risk of injury or property damage.

SOFT START / SOFT CLOSE

The Soft Start / Soft Close feature ramps speed up and down at the start and end of each cycle,

www.ata-america.com

○ Phone: 1-800-934-9892



DOMINATOR^M EASYROLLER 14

TECHNICAL SPECIFICATIONS


Power	Input Voltage	120 Vac / 60Hz
	Standby Power	2.2W
	Motor Type	24V d.c. Permanent Magnet
	Motor Power	100W
	Short-Term Lifting Force	600N
Installation ^{1,2}	Door Size (approx.)	180 ft²
	Door Height (max) ³	14 ft
Transmitter System	Receiver/Transmitter Frequency	Multi-frequency UHF FM (434.37, 433.47 & 433.92MHz)
	Coding System	TrioCode™ 128, code hopping
	Code Combinations	3.4x10 ³⁸ code combinations
	Transmitter Capacity (x 4-button registers)	64
Additional Features	Courtesy Light	2 x LED
	Safety Beam Compatibility	2-wire Safety Beams
	Drum Wheel Adaptor	Suits most doors*
Warranty ⁴	5 year/10,000 cycles on parts ⁴ 1 year on accessories	

^{*}Suits most rolling sheet doors. Not suitable for rolling steel doors

OPTIONAL ACCESSORIES



Wireless Keypad Weather resistance, secure access without a transmitter or keys is great for school kids and active families.



Live Axle Kit: Adaptor kit for Live axle sheet doors.

- ¹ Windy conditions can activate the obstruction feature of the opener.
- ² Suitable for use on dead axle doors.
- ³ Max height 14ft on a door with a 12" drum wheel. Less opening height on a door with a 9.5" drum wheel.
- ⁴ Please see full warranty terms and conditions on our website. This brochure is not evidence of our warranty. Our warranty is in addition to any consumer guarantees that may apply under American Law.

Member of:









SAFETY & SECURITY FEATURES



Soft Start/Soft Close



Intelligent Safety System



Door Profiling



TrioCode™ 128

POWER & MOUNTING SYSTEMS



DC Motor

OPERATING MODES & FEATURES



LED Courtesy Lights



Auto Close



Service Indicator



Vacation Mode



Auxiliary Output

*See our website for our icon glossary explanations.

Automatic Technology America 3626 North Hall Street, Suite 610, Dallas, TX 75219, United States of America



