

AXESS[®] PRO 3300 SERIES



INDUSTRIAL SHUTTER OPENER

Simple, reliable and cost-effective shutter automation.

The Axess[®] Pro Series 3300 range provides simple, reliable and cost-effective shutter automation suitable for up to 50m² in size. Utilising hard-wired 415V power with contactors, these units are designed to be used for many industrial and commercial applications.

Using economical 3-phase 415V hard-wired powerheads with contactor-driven automation, the range includes 1 and 1.5 HP output power options. Both variations can be controlled either by a simple manual console, or the sophisticated logic control system with LCD screen, integrated time clock and TrioCode™128 technology.



WHAT'S INCLUDED:

Opener with various install options

AT A GLANCE:

SECURE & RELIABLE TRANSMITTERS



The TrioCode™128 transmitter system ensures secure and reliable access. It transmits on three frequencies to defeat radio interference, and uses a 128-bit encryption protocol for the ultimate in security.

POWERFUL MOTOR

A powerful 3-phase motor means this opener is both consistent and reliable, and we back this up with a two year warranty*.

LOGIC CONTROLS WITH LCD SCREEN OPTION

The optional integrated logic control system with LCD screen provides scalable functionality, allowing the operation of the opener to be customised specifically to the site's needs.

QUIET, HEAVY DUTY GEARBOX

The high stepdown ratio gearing, immersed in a breatherless oil bath inside the cast aluminium gearbox, provides power and reliability with minimal noise.

TECHNICAL SPECIFICATIONS



AXESS® PRO - 3300 SERIES

Power	Input Voltage	415V a.c. 3-phase
	Standby Power	2.8W
	Motor Type	Contactors
	Motor Power	1.0 HP - 750W 1.5 HP - 1125W
	Controller Fuse	3 x 10A
	Rated Duty Cycle	60%
	Rated Door Area	1.0 HP - 36m ² 1.5 HP - 50m ²
	Typical Travel Speed (shutter dependent)	approx. 200mm/sec
Transmitter System	Receiver/Transmitter Frequency	Multi-frequency UHF FM (433.47, 433.92 & 434.37MHz)
	Coding System	Code hopping (Non-linear encryption algorithm)
	Code Combinations	3.4x10 ³⁸ code combinations (340,282,366,920,938,463,463,374,607,431,768,211,456 codes)
	Transmitter Type	TrioCode™128
	Transmitter Capacity (x 4-button registers)	511
Additional Features (logic control units only)	Courtesy Light	Output Available
	Safety Beam Compatibility	L1 Logics 1x Wireless Safety Beam/2-wire Safety Beam, or 1x 3-Wire Safety Beam L2 Logics 3x Wireless Safety Beam/2-wire Safety Beam
	LCD Screen	Yes
	Warranty*	2 years (parts only)

SAFETY & SECURITY FEATURES

- Soft Start/Soft Stop (inverter units only)
- Door Profiling

POWER & MOUNTING SYSTEM

- 3 Phase Motor

OPERATING MODES

- Service Indicator
- Courtesy Light Output
- Auto Close
- Ventilation Mode
- Vacation Mode
- Time Clock
- AUX Auxiliary Output
- Wireless Safety Beam
- TrioCode™128



ALSO AVAILABLE: LOCKABLE CONTROL BOX

The optional lockable control box mounts the logic or manual console inside an sturdy enclosure. The enclosure features separate Open, Close and Emergency Stop buttons for door control. The Open and Close buttons can be enabled and disabled by the keyed lockout with positions for Auto, Manual and Off operation.

For more product information, visit www.automatictechnology.com/au

©2024 Automatic Technology (Australia) Pty Ltd. All rights reserved. The Automatic Technology logos, feature icons, Axess® & TrioCode™ are registered trademarks. In an ongoing commitment to product quality, the specifications may change from time to time – E&OE Automatic Technology (Australia) Pty Ltd, 6-8 Fiveways Boulevard, Keysborough VIC 3173, www.automatictechnology.com/au, 1300 133 944. *Please see full warranty terms and conditions at www.automatictechnology.com/au. This brochure is not evidence of our warranty. Our warranty is in addition to any consumer guarantees that may apply under the Australian Consumer Law. Date: November 2024

autOmatic
TECHNOLOGY®