aut^omatic TECHNOLOGY

ATS-2 Tempo[™]

As technology and architectural trends evolve, so do our openers. Designed with you in mind, Tempo™ is **FASTER**, **BRIGHTER**, **AND MORE POWERFUL THAN EVER BEFORE**. At its core, Tempo™ features a new, easy to program electronic platform, a supercharged motor, and design updates that will simplify installation.



KEY FEATURES

Tempo™ exceeds Dynamo® GDO-9v3 capabilities

The best in Automatic Technology development history

Superior lifting power, our fastest opening speed ever, and brighter 60W equivalent light

Design updates simplify installation

Hinged cover, clip-on accessory module, pre-wired harness, and quick fit battery compartment

New innovative NextGen platform

3 variable opening speeds (115-150-180mm/sec), supports easy install of transceivers with serial BUS protocol, and PE beam Align Assist function.

INSTALLATION

MEWI

We recommend Tempo[™] be installed with a Steel/Belt or Aluminium/Belt rail for quiet operation



APPLICATION

Residential sectional doors up to 200kg

TECH SPECIFICATIONS

Short term peak force	1100N belt/chain. 1200N tilt
Coding system	TrioCodeTM128, code hopping
Transmitter capacity	64
Safety beams compatibility	2 x wireless or 2-wire

POPULAR ACCESSORIES



Battery Back-Up Wireless Safety
Beams



Wired Safety Beams



Smart Phone Control Kit



Transceiver
(For additional device: gate or garage door opener)



Keypad