AXESS® PRO 1505 SERIES





INDUSTRIAL OVERHEAD OPENER

Lighter. Smaller. Slimmer. Smarter.

The Axess® Pro 1505 upholds Automatic Technology's reputation for reliability, ease of use and integrated technology. Its power-packed and compact design makes it easy to install across a variety of limited-space applications.

The Axess® Pro 1505 opener is a powerful, heavy-duty opener optimally designed to operate high use sectional doors up to 25m². It comes with Automatic Technology's clever Logic Control System featuring LCD screen, customisable menu system and service indicator and can store up to 511 transmitter codes. The Magnetic Automatic Limit Position System (M-ALPS) allows for quick setup and ensures accurate limits are maintained.

WHAT'S INCLUDED:









Opener

2x Remote Control Transmitters

Logic Controls

Wired Safety Beams

AT A GLANCE:

LOGIC CONTROL SYSTEM WITH LCD SCREEN

Customisable menu system, service indicator, 24-hour clock, stores 511 TrioCode™ transmitter codes and integrates additional inputs. Easy plug in. Interfaces with Axess® Pro series products.

MAGNETIC AUTOMATIC LIMIT POSITION SYSTEM (M-ALPS)

Magnetic sensing system for easy set up and maintaining accurate limits as in the Axess® Pro series.

WIRELESS PE BEAM

Wireless Safety Beams available for quicker installation. Wired Safety Beams also available.

QUIET, HEAVY DUTY GEARBOX

Quiet, heavy duty gearbox. Soft start and stop operation.

MOTOR OVERLOAD DETECTION

Adjustable overload detection to protect door and opener if a physical obstruction occurs.

INVERTER DRIVEN 3-PHASE MOTOR

Allows speed control and easy installation.



TECHNICAL SPECIFICATIONS



AXESS® PRO - 1505 SERIES

Warranty*		5 year / 10,000 cycles	
	LCD Screen	Yes	
	Safety Beam Inputs	3	
Additional Features	Safety Beam Compatibility	3 x Wired or Wireless PE Beams (L2 console included)	
	Transmitter Capacity (x 4-button registers)	511	
	Transmitter Type	TrioCode™128	
	Coding System	Code hopping	
Transmitter System	Receiver/Transmitter Frequency	Multi-frequency UHF FM TrioCode™128	
	Typical Travel Speed	Variable via inverter	
	Drive Unit Weight	23kg	
	Rated Duty Cycle	60%	
	Motor Power	373W, 3-phase	
	Motor Type	Induction	
	Standby Power	2.8W	
Power	Input Voltage	230Va.c. 50Hz	
	Max Door Area	25m² wide	25m² wide
	Max Door Height	3.5 metre	5.5 metre
	Track	4 metre	4 metre
Dimensions	ATA Part #	62670	62669

ALSO AVAILABLE:

LOCKABLE CONTROL BOX

The optional lockable control box mounts the logic or manual console inside an sturdy enclosure.

The enclosure features separate Open, Close and Emergency Stop buttons for door control.

The Open and Close buttons can be enabled and disabled by the keyed lockout with positions for Auto, Manual and Off operation.



KEY DIMENSIONS:



