EASY ROLLER® GDO-6 GEN2



RESIDENTIAL ROLLER DOOR OPENER

Simple, compact and slimline roller door opener.

The EasyRoller® builds on decades of innovation to deliver a slim, reliable and secure rolling door opener. Suitable for all residential roller door applications, it is compatible with Automatic Technology's Smart Phone Control Kit and Wireless Safety Beams.

Featuring a strong 600N DC motor, EasyRoller® is designed to reliably lift and lower residential roller doors. The opener comes with TrioCode™128 Remote Controls and bright LED courtesy light for convenience. EasyRoller® features soft start-and-stop functionality reducing door stress and damage to the door, helping it last longer.

WHAT'S INCLUDED:



Opener with LED Courtesy Lights



2x TrioCode™128 transmitters



Wireless Wall Remote

AT A GLANCE:

SECURE & RELIABLE TRANSMITTERS

The TrioCode™128 remote control ensures secure and reliable home access. It transmits on three frequencies to defeat radio interference, and uses a 128-bit encryption protocol for the ultimate in security.

POWERFUL MOTOR

This EasyRoller® 600N DC motor reliably operates doors up to 110kg[^]

LED COURTESY LIGHT

A Courtesy Light means your immediate surrounds can be lit to provide security and convenience, and being an LED light source you know it's going to last.

7 YEAR WARRANTY

The Series 2 EasyRoller® is backed by a 7-year/20,000 cycle warranty*, giving peace of mind.



When maximum spring balanced weight is 20kg.

^{*}Please see full warranty terms and conditions on our website. This brochure is not evidence of our warranty. Our warranty is in addition to any consumer guarantees that may apply under the Australian Consumer Law.

TECHNICAL SPECIFICATIONS



EASY ROLLER® GDO-6 GEN2

Warranty*	7 year/20,000 cycles	
Network Compatible	Ready for Smart Phone Control Kit	
	Safety Beam Compatibility	2 x Wireless Safety Beams or 2-Wire Safety Beams
Additional Features	Courtesy Light	2×LED
	Transmitter Capacity (x 4-button registers)	64
	Code Combinations	3.4x10 ³⁸ code combinations
	Coding System	TrioCode™ 128, code hopping
Transmitter System	Receiver/Transmitter Frequency	Multi-frequency UHF FM (433.47, 433.92 & 434.37MHz)
	Typical Travel Speed	130mm/sec
	Rated Door Area	16.5m²
 Door Sizes	Maximum Door Weight	110kg
	Motor Power	100W
	Motor Type	24V d.c. Permanent Magnet
	Standby Power	2.2W
	Transformer Rating	100VA
Power	Input Voltage	230-240V a.c. 50Hz

SAFETY & SECURITY **FEATURES**



Soft Start/Soft Stop



Intelligent Safety System



Door Profiling



TrioCode™128

POWER & MOUNTING SYSTEM



DC Motor - 1000N



Slim Fit

OPERATING MODES



Wireless Safety Beam



Service Indicator



LED Courtesy Lights





Ventilation Mode



Time Clock



Auto Close



Vacation Mode



AUX Auxiliary Output

OPTIONS AND UPGRADES



SMART PHONE CONTROL KIT

Monitor and operate your garage door and gate on your smart phone from anywhere*. Control multiple locations from the one app, such as home and holiday home. Receive push notifications about the status of your garage door and gate, view past activities, set various opening modes, customise user settings and more in the Automatic Technology App.



BATTERY BACK UP

In the event of power failure, your door will still operate.



WIRELESS SAFETY BEAMS

Protect your family and possessions by detecting obstructions while your door is closing.



SMARTSOLAR™ READY

Using only one solar panel the sun does all the work for you.

